



Moorestown Standard/Passage Cremone Bolt

Includes Moorestown Suited Trim

BOL136-84	Moorestown Standard Cremone Bolt for 7'0 Door
BOL136-96	Moorestown Standard Cremone Bolt for 8'0 Door
BOL136-120	Moorestown Standard Cremone Bolt for 10'0 Door

Cremone Bolt Accessories

2100-AS	Optional Angle Strike
ACC171	Moorestown Box Strike
9931-020	Single Sided 2.0" Spindle
9941-045	Double Sided 4.5" Spindle
2700-06A	Double Sided 6.0" Spindle for Thick Doors 3" Max Thickness

Supplied Standard



2100-US
Universal Strike



9931-020
Single Spindle

Optional Accessories



2100-AS
Angle Strike



ACC171
Moorestown Box Strike

Moorestown Standard/Passage Cremone Bolt



Features:

Von Morris Moorestown Cremone Bolts feature a solid brass case CNC milled from brass billet and guides with an internal mechanism of brass and stainless steel. The Standard Cremone case is very narrow, less than 1.5", for use on narrow stiles of French doors and windows. Cremone case contains a cassette mechanism that can be handed simply by reversing the cassette. The Cremone can also be easily changed from lever operation (90° rotation) to knob operation (180°) simply by relocating the spindle. Shoot Bolts are attached to the Cremone mechanism with machine screws. **Price Includes a half pair of Small Moorestown Levers or Knobs.**

Guides:

End Guides have a flat spring operating on the front of the bolt to prevent rattling. The length of the Guide and placement of the spring conceals any scratches on the bolt caused by the spring. This End Guide design allows the bolts to be installed on the door and then cut to length at the job site.

Standard Cremone Case Size:

Length of Cassette:	10.5"
Width:	1.5"
Height to edge of case:	0.787"
Height to face of knob/lever boss:	1.024"

Spindle Height: Standard Spindle height is 42".

Standard Lengths: 7', 8' and 10'. Other sizes by special order.
Bolts can be cut to size at job site.

Hub Rotation: Knob - 180° rotation. Lever - 90° rotation.

Throw: Knob Operation – 1.00" Lever Operation – 0.75"

Spindle: Cremones are supplied with a special spindle for double sided operation

Bolts:
Bottom bolt: 0.625" wide x 40.01"
Top bolt: 0.625" wide x 40.03" for a 7.0' Door
Top bolt: 0.625" wide x 52.92" for a 8.0' Door
Top bolt: 0.625" wide x 76.92" for a 10.0' Door

Strikes: Cremone Bolts are supplied with Mortise and Universal strikes. Angle strikes and Box strikes are available at an additional cost.